# Aastra 675xi RP Phones

| | 6751i RP | 6753i RP | 6757i CT RP |
|---|---|---|---|
| **Telephone Features** | | | |
| Number of lines | 1 | 6 | 9 |
| Multi-user assignment | | Y | Y |
| Programmable functions (hard keys/softkeys) | 9* (0/0) | 6 (6/0) | 30 (0/12) |
| Pre-programmed feature keys | 8 | 8 | 8 |
| Compatible with M670i (536M)[2] expansion module | | Y | Y |
| Compatible with M675i (560M)[2] expansion module | | | Y |
| Full-duplex speakerphone | Y | Y | Y |
| Dedicated headset jack | | Y | Y |
| Display screen size | 3 lines x 16 characters | 3 lines x 16 characters | 144 x 128 pixels |
| Backlit display | | Y | Y |
| Adjustable display contrast | Y | Y | Y |
| Visual message waiting indication | Y | Y | Y |
| 3-Way conference | Y | Y | Y |
| Redial, Call Hold, Call mute | Y | Y | Y |
| Do not disturb (DND) | Y | Y | Y |
| Caller and calling line information | Y | Y | Y |
| Call waiting display | Y | Y | Y |
| Call forward, transfer | Y | Y | Y |
| Missed call indicator | Y | Y | Y |
| Callers log Name/Number capacity | 200 | 200 | 200 |
| Last Number Redial Name/Number capacity | 100 | 100 | 100 |
| Call park/pickup | Y | Y | Y |
| Built-in cordless mobility | | | WDCT 2.4 GHz FH-SS |
| **Power Options** | | | |
| Power over Ethernet (IEEE 802.3 af) support | Y | Y | Y |
| Optional mid-span PoE injector support | Y | Y | Y |
| AC wall adapter (Included) | Y | Y | Y |
| **Configuration & Administration** | | | |
| Microsoft Response Point Administrator | Y | Y | Y |
| Microsoft Response Point Assistant | Y | Y | Y |
| Telephone User Interface | Y | Y | Y |
| Web User Interface | Y | Y | Y |
| **Network Support** | | | |
| 10/100 Mbps Auto-Sensing Switched Ethernet ports | 2 | 2 | 2 |
| 802.1p/q VLAN tagging & QOS | Y | Y | Y |
| IETF DHCP | Y | Y | Y |
| IETF NTP | Y | Y | Y |
| **Protocol Support** | | | |
| IETF SIP (RFC3261) | Y | Y | Y |
| XML API support | Y | Y | Y |
| **Codecs** | | | |
| G.711µ-law/A-law | Y | Y | Y |
| G.729 | Y | Y | Y |

* Programmable number pad speedial

[2] Some products may reflect former name

Rev 07/08

COPYRIGHT (C) 2008 AASTRA TECHNOLOGIES LTD. ALL RIGHTS RESERVED. INFORMATION IN THIS DOCUMENT IS SUBJECT TO CHANGE WITHOUT NOTICE. AASTRA TELECOM ASSUMES NO RESPONSIBILITY FOR ANY ERRORS THAT MAY APPEAR IN THIS DOCUMENT. PRODUCT CAPABILITIES DESCRIBED IN THIS DOCUMENT PERTAIN SOLELY TO AASTRA TELECOM'S MARKETING ACTIVITIES IN THE U.S AND CANADA. AVAILABILITY IN OTHER MARKETS MAY VARY.

AASTRA IS A REGISTERED TRADEMARK OF AASTRA TECHNOLOGIES LTD. MICROSOFT, MICROSOFT OFFICE OUTLOOK AND RESPONSE POINT ARE TRADEMARKS OF THE MICROSOFT GROUP OF COMPANIES IN THE UNITED STATES AND/OR OTHER COUNTRIES

AASTRA TELECOM
155 SNOW BLVD.,
CONCORD, ONTARIO, CANADA, L4K 4N9
SALES@AASTRA.COM • WWW.AASTRATELECOM.COM

Microsoft® Response Point™

AASTRA

Downloaded from www.Manualslib.com manuals search engine